



WORKSWELL WIRIS MINI

Datasheet

Company contact details

Mobile: +420 602 540 331

E-mail: info@workswell.eu

Web: www.drone-thermal-camera.com



WIRIS MINI technical specification

Thermal Imaging Camera	
Resolution	384 x 288 pixels
Temperature ranges	-10 °C to +250 °C
Temperature sensitivity	0.05 °C (50 mK)
Accuracy	±2 % or ±2 °C
Spectral range	8 – 14 μm, Uncooled VOx microbolometer
Calibration	Yes, the package includes the calibration certificate
Lenses	Interchangeable and focusable, various field of view
2 lenses in the package	71° (6.8mm) and 35° (13mm), exchangeable
Focus	Manual (focused on infinity, Min focus distance depends on lens)
Digital zoom in IR	12x
Digital Camera	
Resolution	1600 x 1200 pixels
Focus and zoom	Fixed, 16x digital
Remote control & Video output	
Digital interfaces	PWM, S.BUS, USB 2.0 (data transfer, WIRIS Mini update and control)
Video output	Digital HDMI (1280 x 1024px), Analogue Video (NTSC, PAL)
Memory and data recording	
Image recording	Radiometric JPEG, Radiometric TIFF, Non-Radiometric, Digital camera JPEG
Video recording	No
GPS tagging	Yes, MavLink or GPS serial communication
Software	Internal / Micro SD card slot
Measurement functions	
Measurement functions	Max temperature, Min temperature
Emissivity correction	Yes
Power supply & dimensions	
Input supply voltage	7 – 32 V DC (< 6W power dissipation)
Dimensions and weight	85 x 65 x 45 mm, <250g

